

EPIC PRO

CHF 7,999.00



Gloss Vivid Pink/Pro Blue/Metallic White Silver

Konkurrenzfähig? Versteht sich doch von selbst. Das Epic Pro ist ein Bike ohne Limits. Wir haben unser bekanntes Epic-Chassis - das effizienteste und leistungsfähigste XC-Racebike auf dem Markt - mit Komponenten versehen, die unter den brutalsten Bedingungen funktionieren, Saison für Saison.

EPIC PRO	S	M	L	XL
Stack (mm)	588	597	611	630
Reach (mm)	408	433	456	475
Steuerrohrlänge (mm)	95	105	120	140
Steuerrohrwinkel (degrees)	69.5	69.5	69.5	69.5
Tretlagerhöhe (mm)	332	332	332	332
Tretlagerabsenkung (mm)	38.9	38.9	38.9	38.9
Nachlauf (mm)	94	94	94	94
Gabellänge, gesamt (mm)	506	506	506	506
Gabelversatz / Offset (mm)	42	42	42	42
Mitte Tretlager - Mitte V.-achse (mm)	659	687	715	742
Kettenstreben-Länge (mm)	438	438	438	438
Radstand (mm)	1094	1123	1151	1177
Oberrohrlänge horizontal (mm)	568	596	623	647
Überstandshöhe (mm)	764	770	776	799
Sitzrohrlänge (mm)	400	434	470	520
Sitzrohrwinkel (degrees)	74.75	74.75	74.75	74.75
Kurbellänge (mm)	170	175	175	175
Lenkerbreite (mm)	760	760	760	760
Vorbauhöhe (mm)	60	70	80	90
Sattellbreite (mm)	155	143	143	143
Länge Sattelstütze (mm)	350	400	400	400

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Specialized FACT 11m, XC Geometry, Rider-First Engineered™, threaded BB, 12x148mm rear spacing, internal cable routing, 100mm of travel
DÄMPFER	Custom RockShox Micro Brain shock w/ Spike Valve, AUTOSAG, 51x257mm
GABEL	RockShox SID Brain 29, Solo Air, Position Sensitive, top-adjust Brain Fade, 15x110mm Maxle® Stealth thru-axle, 42mm offset, 100mm of travel
VORBAU	Specialized XC, 3D-forged alloy, 4-bolt, 6-degree rise
LENKER	S-Works Carbon XC Mini Rise, 6-degree upsweep, 8-degree backsweep, 10mm rise, 760mm, 31.8mm
LENKERGRIFFE	Specialized Trail Grips
BREMSE VORNE	SRAM Level TLM, hydraulic disc
BREMSE HINTEN	SRAM Level TLM, hydraulic disc
SCHALTWERK	SRAM X01 Eagle, 12-speed
SCHALTHEBEL	SRAM X01 Eagle, trigger, 12-speed
KASSETTE	SRAM XG-1295 Eagle, 12-speed, 10-50t
KETTE	SRAM GX Eagle, 12-speed
KURBELGARNITUR	SRAM X1 carbon Eagle, Boost™ 148, DUB, 170/175mm, 32T
KETTENBLÄTTER	Alloy, 32T
INNENLAGER	SRAM DUB, threaded BB
FELGEN	Roval Control Carbon, 25mm internal width, tubeless-ready
VORDERRADNABE	Specialized, sealed cartridge bearings, 15x110mm spacing, 28h
HINTERRADNABE	DT Swiss 350, Star Ratchet, 36t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPEICHEN	DT Swiss Industry
VORDERREIFEN	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
HINTERREIFEN	Fast Trak, Control casing, GRIPTON® compound, 60 TPI, 2Bliss Ready, 29x2.3"
SATTEL	Body Geometry Power, Hollow Titanium rails, 143mm
SATTELSTÜTZE	Carbon, single-bolt, 30.9mm

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
90320-1002	EPIC PRO CARBON 29	Gloss Vivid Pink/Pro Blue/Metallic White Silver	S
90320-1003			M
90320-1004			L
90320-1005			XL