

PITCH COMP 2X

CHF 699.00



Gloss Uv Lilac/Satin Black



Satin Black/Summer Blue/Hyper



Satin Gunmetal/Taupe



Satin Storm Grey/Golden Yellow/Black

Das robuste Pitch Comp wurde entwickelt, um dich bei jedem Abenteuer zu unterstützen. Wir haben das Handling des Bikes unermüdlich verfeinert, um ein exquisites Gleichgewicht aus agilem, spielerischem Gefühl und Stabilität bei hoher Geschwindigkeit in einem bewährten Rahmendesign zu erreichen.

SPECS	Technische Änderungen vorbehalten.
RAHMEN	A1 Premium Aluminum, Sport Trail 27.5 Geometry, zero-stack head tube, internal cable routing, 135x9mm forged dropouts, chainstay-mounted disc brake, replaceable alloy derailleur hanger
GABEL	SR Suntour XCM 27.5 w/HLO, coil, custom Multi-Circuit damping, 80/100mm of travel (size-specific)
VORBAU	Stout 3D-forged alloy, 31.8mm, 6-degree rise
LENKER	Specialized, alloy, 9-degree backsweep, 15mm rise, 31.8mm
LENKERGRIFFE	Specialized MTB Grip, lock-on
BREMSE VORNE	Shimano BR-MT200, hydraulic disc, 180/160mm
BREMSE HINTEN	Shimano BR-MT200, hydraulic disc, 160mm
UMWERFER	Shimano Altus FD-M2020 2-speed
SCHALTWERK	Shimano Acera, 9-speed
SCHALTHEBEL	Shimano Altus, 9-speed
KASSETTE	SunRace, 9-Speed, 11-36t
KETTE	KMC X9EPT, 9-speed, anti-corrosion coating w/ reusable Missing Link™
KURBELGARNITUR	Stout 2x, forged alloy
KETTENBLÄTTER	36/22T
INNENLAGER	Square-tapered, 73mm, internal bearings
FELGEN	Stout Trail 27.5, alloy, disc only, double-wall, 25mm inner width, 32h
VORDERRADNABE	Shimano, Center Lock™ disc, 9x100mm spacing, quick-release, 32h
HINTERRADNABE	Shimano, Center Lock™ disc, 9x135mm spacing, quick-release, 32h
SPEICHEN	Stainless, 14g
VORDERREIFEN	Ground Control Sport, 60 TPI, wire bead, Flak Jacket Flat protection, 27.5 x 2.3"
HINTERREIFEN	Ground Control Sport, 60 TPI, wire bead, Flak Jacket Flat protection, 27.5 x 2.3"
SATTELSTÜTZE	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PITCH COMP 2X	XS	S	M	L	XL
Stack (mm)	562	562	585	604	618
Reach (mm)	380	400	420	440	460
Steuerrohrlänge (mm)	95	95	100	120	135
Steuerrohrwinkel (degrees)	68.5	68.5	68.5	68.5	68.5
Tretlagerhöhe (mm)	310	310	310	310	310
Tretlagerabsenkung (mm)	43	43	43	43	43
Nachlauf (mm)	94	94	94	94	94
Gabellänge, gesamt (mm)	475	475	495	495	495
Gabelversatz / Offset (mm)	42	42	42	42	42
Mitte Tretlager - Mitte V.-achse (mm)	631	651	680	708	733
Kettenstreben-Länge (mm)	435	435	435	435	435
Radstand (mm)	1063	1083	1112	1139	1165
Oberrohrlänge horizontal (mm)	542	572	599	625	649
Überstandshöhe (mm)	660	690	739	766	808
Sitzrohrlänge (mm)	310	360	415	450	510
Sitzrohrwinkel (degrees)	74	73	73	73	73
Kurbellänge (mm)	165	170	170	175	175
Lenkerbreite (mm)	720	720	740	740	740
Vorbauhöhe (mm)	35	45	45	60	60
Sattellbreite (mm)	155	155	143	143	143
Länge Sattelstütze (mm)	350	350	350	400	400

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
95920-5001	PITCH COMP 27.5 2X INT	UVLLC/BLK	XS
95920-5003			M
95920-5004			L
95920-5005			XL
95920-5101	PITCH COMP 27.5 2X INT	BLK/SUMMER BLUE/HYP	XS
95920-5102			S
95920-5103			M
95920-5104			L
95920-5105			XL
95920-5201	PITCH COMP 27.5 2X INT	GUN/TPE	XS
95920-5202			S
95920-5203			M
95920-5204			L
95920-5205			XL
95920-5301	PITCH COMP 27.5 2X INT	STRMGRY/GOLDEN YELLOW/BLK	XS
95920-5302			S

PITCH COMP 2X

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
95920-5303	PITCH COMP 27.5 2X INT	STRMGRY/GOLDEN YELLOW/BLK	M
95920-5304			L
95920-5305			XL