

# SIRRUS EQ STEP-THROUGH - BLACK TOP LTD

CHF 949.00



Satin Cast Black/Acid Lava

Um deine Fitnessziele zu realisieren, brauchst du einen Partner, auf den du dich jederzeit verlassen kannst. Du brauchst das Sirrus EQ - Black Top LTD! Als Step-Through Variante mit tiefem Einstieg funktioniert das Auf- und Absteigen einfach und unkompliziert.

- Unser leichter Rahmen aus A1 SL Premium Aluminium mit entspannter Fitness-Geometrie sorgt für eine direkte Kraftübertragung und fährt sich dennoch erstaunlich komfortabel. Plug&Play Aufnahmen erlauben die einfache Montage von Schutzblechen, ein Gepäckträger lässt sich ebenso anbringen.
- Hydraulische Promax F1 Scheibenbremsen garantieren eine konsistente, griffige Bremswirkung.
- Der vordere Shimano Dynamo-Hub beherbergt ein Energieproduktionssystem, das dein Frontlicht durch die ganze Nacht hindurch und länger antreibt.

## SIRRUS EQ STEP-THROUGH - BLACK TOP LTD

	S	M	L
Stack (mm)	536	561	590
Reach (mm)	373	383	393
Steuerrohrlänge (mm)	124	146	176
Steuerrohrwinkel (degrees)	70	71	71
Tretlagerhöhe (mm)	275	275	275
Tretlagerabsenkung (mm)	70	70	70
Nachlauf (mm)	71	65	65
Gabellänge, gesamt (mm)	390	390	390
Gabelversatz / Offset (mm)	51	51	51
Mitte Tretlager - Mitte V.-achse (mm)	601	610	630
Kettenstreben-Länge (mm)	440	440	440
Radstand (mm)	1031	1040	1060
Oberrohrlänge horizontal (mm)	532	549	568
Überstandshöhe (mm)	615	625	625
Sitzrohrlänge (mm)	400	450	500
Sitzrohrwinkel (degrees)	73.5	73.5	73.5
Kurbellänge (mm)	165	170	170
Lenkerbreite (mm)	580	580	600
Vorbaulänge (mm)	80	90	100
Sattelbreite (mm)	155	155	143
Länge Sattelstütze (mm)	300	350	350

SPECS	Technische Änderungen vorbehalten.
RAHMEN	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully manipulated butted tubing, internal cable routing, flat-mount disc, quick-release, Plug + Play rack/fender mounts
GABEL	Steel, 1-1/8" steerer, QR, flat-mount disc, Plug + Play rack & fender mounts
LENKER	Double-buttet alloy, 9-degree backsweep, 31.8mm
LENKERBAND	Body Geometry Contour, lock-on
SATTEL	Bridge Sport Thick, steel rails
SATTELSTÜTZE	Alloy, 12mm offset, 2-bolt clamp, 27.2mm
BREMSE VORNE	Promax F1, hydraulic disc, flat-mount, 160mm
BREMSE HINTEN	Promax F1, hydraulic disc, flat-mount, 140mm
SCHALTHEBEL	Shimano Acera, 8-speed
UMWERFER	Shimano Tourney, 3-speed, top-swing
SCHALTWERK	Shimano Altus, 7-/8-speed
KASSETTE	Shimano Altus, 8-speed, 11-32t
KURBELGARNITUR	Shimano Tourney, TY501
KETTENBLÄTTER	48/38/28T
INNENLAGER	BSA, square-taper, 68mm
KETTE	KMC X8 w/ Missing Link™, 8-speed
FELGEN	700C disc, 22mm rim depth, 21mm internal width
VORDERRADNABE	Shimano Dynamo, 6-bolt disc, 100mm spacing, quick-release, 32h
HINTERRADNABE	Alloy, 6-bolt disc, 8-/9-speed freehub, loose ball bearing, quick-release, 32h
SPEICHEN	Stainless, 14g
VORDERREIFEN	Specialized Nimbus II Sport Reflect, 60TPI, wire bead w/ Black Belt protection, 700x32mm
HINTERREIFEN	Specialized Nimbus II Sport Reflect, 60TPI, wire bead w/ Black Belt protection, 700x32mm
SCHEINWERFER	Herrmans H-Flow, w/ on/off
RÜCKLICHT	Herrmans H-Trace Mini
KETTENKASTEN	Included w/ crankset
STÄNDER	Center-mount, alloy
GEPÄCKTRÄGER	15kg rating, compatible w/ RackTime SnapIt system
SCHUTZBLECHE	Specialized DryTech, metal, stainless steel hardware

ART.-NR.	BESCHREIBUNG	FARBE	GRÖSSE
92920-7802	SIRRUS EQ STEP THROUGH BT INT	Satin Cast Black/Acid Lava	S
92920-7803			M
92920-7804			L